

## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca








Safety Data Sheet dated 28/6/2017, version 2

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier  
Mixture identification:  
Trade name: Finitura craquelé Bianca  
Trade code: ES1011
- 1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended use: Surface coating  
---
- 1.3. Details of the supplier of the safety data sheet  
Company:  
  
Sirca S.p.A.  
Address:  
Viale Roma, 85  
35010 S.Dono di Massanzago (PD) - ITALY  
Tel. +39 0499322311  
Competent person responsible for the safety data sheet:  
safety@sirca.it
- 1.4. Emergency telephone number  
  
Sirca S.p.A. +39 049 9322311 (08.00 - 17.00) From Monday to Friday

#### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture  
EC regulation criteria 1272/2008 (CLP):  
 Danger, Flam. Liq. 2, Highly flammable liquid and vapour.  
 Warning, Skin Irrit. 2, Causes skin irritation.  
 Warning, Eye Irrit. 2, Causes serious eye irritation.  
 Warning, STOT SE 3, May cause respiratory irritation.  
 Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- Adverse physicochemical, human health and environmental effects:  
No other hazards known
- 2.2. Label elements  
Hazard pictograms:



- Danger
- Hazard statements:  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements:  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P370+P378 In case of fire: Use CO2, Foam, Chemical powders to extinguish.
- Special Provisions:  
None
- Contains  
xylene [isomer mixture]  
4-methylpentan-2-one; isobutyl methyl ketone  
Fatty acids, C14-18 and C16-18-unsatd., maleated: May produce an allergic reaction.  
Fatty acids, C18-unsatd., trimers, compds. with oleylamine: May produce an allergic reaction.
- Special provisions according to Annex XVII of REACH and subsequent amendments:  
None
- 2.3. Other hazards  
  
Other Hazards:  
No other hazards known

## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

#### SECTION 3: Composition/information on ingredients

##### 3.1. Substances

N.A.

##### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 25% - < 48% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 5% - < 7% ethylbenzene

REACH No.: 01-2119489370-35-xxxx, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.1/4/Inhal Acute Tox. 4 H332

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.10/1 Asp. Tox. 1 H304

>= 3% - < 5% 4-methylpentan-2-one; isobutyl methyl ketone

REACH No.: 01-2119473980-30-xxxx, Index number: 606-004-00-4, CAS: 108-10-1, EC: 203-550-1

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.1/4/Inhal Acute Tox. 4 H332

EUH066

>= 3% - < 5% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29-xxxx, Index number: 607-195-00-7, CAS: 108-65-6, EC: 203-603-9

⚠ 2.6/3 Flam. Liq. 3 H226

>= 1% - < 2% butanone

REACH No.: 01-2119457290-43-xxxx, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 0.5% - < 1% ethyl acetate

REACH No.: 01-2119475103-46-xxxx, Index number: 607-022-00-5, CAS: 141-78-6, EC: 205-500-4

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 0.25% - < 0.5% sec-butyl acetate

REACH No.: 01-2119488971-22-xxxx, Index number: 607-026-00-7, CAS: 110-19-0, EC: 203-745-1

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 0.1% - < 0.2% Fatty acids, C14-18 and C16-18-unsatd., maleated

REACH No.: 01-2119976378-19-xxxx, CAS: 85711-46-2, EC: 288-306-2

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.4/2/1 Skin Sens. 1 H317

>= 0.05% - < 0.06% Fatty acids, C18-unsatd., trimers, compds. with oleylamine

REACH No.: 01-2119974148-28-xxxx, CAS: 85711-55-3, EC: 288-315-1

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1A Skin Sens. 1A H317

⚠ 3.9/2 STOT RE 2 H373

>= 0.0015% - < 0.05% 2,6-dimethylheptan-4-one; di-isobutyl ketone

REACH No.: 01-2119474441-41-xxxx, Index number: 606-005-00-X, CAS: 108-83-8, EC: 203-620-1

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H335

## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

---

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.  
Wash thoroughly the body (shower or bath).  
Remove contaminated clothing immediately and dispose off safely.  
After contact with skin, wash immediately with soap and plenty of water.

###### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.  
Protect uninjured eye.

###### In case of Ingestion:

Induce vomiting only on doctor's advice

###### In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

##### 4.2. Most important symptoms and effects, both acute and delayed

Contact a poisons centre

##### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media:

In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

##### 5.2. Special hazards arising from the substance or mixture

Combustion may liberate toxic or very toxic gases. Do not breathe fumes.

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

##### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

##### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

##### 6.3. Methods and material for containment and cleaning up

Collect the spilled product with no-sparking tools.

Rapidly recover the product. To do so, wear a mask and protective clothing.

Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.

After the product has been recovered, rinse the area and materials involved with water.

##### 6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

Keep away from flame and sparks. Avoid accumulating electrostatic charge.

Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

Do not smoke while working.

See also section 8 for recommended protective equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

#### 7.3. Specific end use(s)

No further recommendations. Refer to point 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

xylene [isomer mixture] - CAS: 1330-20-7

(OEL (IT)) - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: pelle

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4

(OEL (IT)) - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Behaviour: Binding - Notes: pelle

EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

(OEL (IT)) - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding

EU - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm

ACGIH - TWA(8h): 20 ppm - STEL: 75 ppm - Notes: A3, BEI - URT irr, dizziness, headache

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

(OEL (IT)) - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: Pelle

EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

butanone - CAS: 78-93-3

(OEL (IT)) - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm - Behaviour: Binding

EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm

ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

ethyl acetate - CAS: 141-78-6

(OEL (IT)) - TWA: 400 ppm

ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr

sec-butyl acetate - CAS: 110-19-0

Québec - TWA: 712.64 mg/m<sup>3</sup>, 150 ppm

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

2,6-dimethylheptan-4-one; di-isobutyl ketone - CAS: 108-83-8

ACGIH - TWA(8h): 25 ppm - Notes: URT and eye irr

### DNEL Exposure Limit Values

xylene [isomer mixture] - CAS: 1330-20-7

Worker Industry: 180 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 108 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1872 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 12.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4

Worker Industry: 180 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 293 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 77 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Worker Industry: 208 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

Worker Industry: 208 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 11.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

Worker Industry: 83 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term (repeated)

Worker Industry: 83 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 155.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 155.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 4.2 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

Consumer: 14.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term (repeated)

Consumer: 4.2 mg/kg - Exposure: Human Oral - Frequency: Long Term (repeated)

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Professional: 153.5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 275 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 54.8 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethyl acetate - CAS: 141-78-6

Worker Industry: 1468 mg/m<sup>3</sup> - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 1468 ppm - Exposure: Human Inhalation - Frequency: Short Term (acute)

## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

Worker Industry: 63 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects  
 Worker Industry: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 4.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects  
 Consumer: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute)  
 Consumer: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 37 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, local effects  
 Consumer: 367 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects  
 Consumer: 367 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

sec-butyl acetate - CAS: 110-19-0  
 Worker Industry: 4.95 mg/Kg-bw/day - Consumer: 2.48 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 243 mg/m3 - Consumer: 60.3 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 2.48 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

2,6-dimethylheptan-4-one; di-isobutyl ketone - CAS: 108-83-8  
 Worker Industry: 290 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 80 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 479 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 145 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Consumer: 28.5 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 282 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 7.14 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

xylene [isomer mixture] - CAS: 1330-20-7  
 Target: Fresh Water - Value: 0.327 mg/l  
 Target: Fresh Water - Value: 0.327 mg/l  
 Target: occasional emission - Value: 0.327 mg/l  
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  
 Target: Soil (agricultural) - Value: 2.31 mg/kg - Notes:: dry  
 Target: Marine water sediments - Value: 12.46 mg/kg - Notes:: dry  
 Target: Freshwater sediments - Value: 12.46 mg/kg - Notes:: dry

ethylbenzene - CAS: 100-41-4  
 Target: Fresh Water - Value: 0.1 mg/l  
 Target: Marine water - Value: 0.01 mg/l  
 Target: Marine water sediments - Value: 13.7 mg/l  
 Target: Freshwater sediments - Value: 13.7 mg/l  
 Target: occasional emission - Value: 0.1 mg/l

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Target: Fresh Water - Value: 0.6 mg/l  
 Target: Marine water - Value: 0.06 mg/l  
 Target: Freshwater sediments - Value: 8.27 mg/kg  
 Target: Marine water sediments - Value: 0.83 mg/kg  
 Target: Soil (agricultural) - Value: 1.3 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 Target: Fresh Water - Value: 0.635 mg/l  
 Target: Marine water - Value: 0.0635 mg/l  
 Target: Marine water sediments - Value: 0.329 mg/kg - Notes:: dry  
 Target: Freshwater sediments - Value: 3.29 mg/kg - Notes:: dry  
 Target: Soil (agricultural) - Value: 0.29 mg/kg - Notes:: dry  
 Target: STP - Value: 100 mg/l

ethyl acetate - CAS: 141-78-6  
 Target: Fresh Water - Value: 0.26 mg/l  
 Target: Marine water - Value: 0.026 mg/l  
 Target: Freshwater sediments - Value: 1.25 mg/kg  
 Target: Marine water sediments - Value: 0.125 mg/kg  
 Target: Soil (agricultural) - Value: 0.24 mg/kg  
 Target: orally (secondary poisoning) - Value: 200 mg/kg - Notes:: Dietetico  
 Target: STP - Value: 650 mg/l

sec-butyl acetate - CAS: 110-19-0  
 Target: Fresh Water - Value: 0.17 mg/l  
 Target: Marine water - Value: 0.017 mg/l  
 Target: Freshwater sediments - Value: 0.877 mg/kg  
 Target: Marine water sediments - Value: 0.0877 mg/kg  
 Target: Soil (agricultural) - Value: 0.0755 mg/kg

2,6-dimethylheptan-4-one; di-isobutyl ketone - CAS: 108-83-8  
 Target: Fresh Water - Value: 0.03 mg/l  
 Target: Marine water - Value: 0.003 mg/l  
 Target: occasional emission - Value: 0.3 mg/l  
 Target: Freshwater sediments - Value: 0.46 mg/kg  
 Target: Marine water sediments - Value: 0.046 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 2.55 mg/l  
 Target: Soil (agricultural) - Value: 0.0746 mg/kg

#### 8.2. Exposure controls



## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Because of the synergetic effect of the substances contained in the formulation it is not possible to identify a unique material that can resist to their fusion. Multi - layer protective gloves can be suitable for mixes of substances. Pay attention to the data about grade of protection and of permeation rate furnished by the producer of the gloves about the substances listed on point 3 of this sheet.

Respiratory protection:

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

Thermal Hazards:

None known

Environmental exposure controls:

None known

Appropriate engineering controls:

None

---

#### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

|   |                     |
|---|---------------------|
| Appearance and colour:                        | liquid              |
| Odour:  | characteristic      |
| Odour threshold:                              | N.A.                |
| pH:   | N.A.                |
| Melting point / freezing point:               | < 1°C               |
| Initial boiling point and boiling range:      | > 55°C              |
| Solid/gas flammability:                       | N.A.                |
| Upper/lower flammability or explosive limits: | N.A.                |
| Vapour density:                               | N.A.                |
| Flash point:                                  | < 23°C (< 73.4 °F)  |
| Evaporation rate:                             | N.A.                |
| Vapour pressure:                              | N.A.                |
| Relative density:                             | 1.3250 Kg/l a 20°C  |
| Solubility in water:                          | N.A.                |
| Solubility in oil:                            | N.A.                |
| Partition coefficient (n-octanol/water):      | N.A.                |
| Auto-ignition temperature:                    | > 250°C             |
| Decomposition temperature:                    | N.A.                |
| Viscosity (typical value):                    | 50.00 " Din cup # 4 |
| Explosive properties:                         | N.A.                |
| Oxidizing properties:                         | N.A.                |

9.2. Other information

|                                      |      |
|--------------------------------------|------|
| Miscibility:                         | N.A. |
| Fat Solubility:                      | N.A. |
| Conductivity:                        | N.A. |
| Substance Groups relevant properties | N.A. |

---

#### SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

vapours potentially dangerous to health may be released.

---

#### SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

xylene [isomer mixture] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg

ethylbenzene - CAS: 100-41-4

## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

- a) acute toxicity:  
Test: LD50 - Route: Skin - Species: Rabbit = 15400 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 4000 Ppm - Duration: 4h
- d) respiratory or skin sensitisation:  
Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Negative
- 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
- a) acute toxicity:  
Test: LC50 - Route: Inhalation - Species: Rat = 23.29 g/m3  
Test: LD50 - Route: Oral - Species: Rat = 2080 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 8.2 mg/l - Duration: 4h  
Test: LD50 - Route: Skin - Species: Rabbit = 2000 mg/kg
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 8532 mg/kg  
Test: LC50 - Route: Skin - Species: Rat > 5000 mg/kg  
Test: LC50 - Route: Inhalation Mist - Species: Rat > 23.8 mg/l - Duration: 6h
- b) skin corrosion/irritation:  
Test: Skin Irritant - Route: Skin - Species: Rabbit Negative
- butanone - CAS: 78-93-3
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 2737 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit = 6480 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h
- b) skin corrosion/irritation:  
Test: Skin Corrosive - Species: Rabbit Negative - Notes: moderatamente irritante
- ethyl acetate - CAS: 141-78-6
- a) acute toxicity:  
Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg  
Test: LD50 - Route: Oral - Species: Rat = 5620 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat > 29.3 mg/l - Duration: 4h  
Test: LD50 - Route: Oral - Species: Rabbit = 4934 mg/kg body weight
- b) skin corrosion/irritation:  
Test: Skin Irritant - Route: Skin - Species: Rabbit Negative
- e) germ cell mutagenicity:  
Test: Genotoxicity Negative
- j) aspiration hazard:  
Test: Respiratory Tract Corrosive - Route: Inhalation Positive
- sec-butyl acetate - CAS: 110-19-0
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat 13413 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 17400 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat > 30 mg/l - Duration: 6h
- Fatty acids, C14-18 and C16-18-unsatd., maleated - CAS: 85711-46-2
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat Female > 2000 mg/kg
- b) skin corrosion/irritation:  
Test: Skin Irritant Yes  
Test: Eye Irritant - Species: Rabbit No
- d) respiratory or skin sensitisation:  
Test: Skin Sensitization - Species: Mouse Yes

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

xylene [isomer mixture] - CAS: 1330-20-7

- a) Aquatic acute toxicity:  
Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 48  
Endpoint: LC50 - Species: Fish = 3.2 mg/l - Duration h: 96  
Endpoint: LC50 - Species: Algae = 2.6 mg/l - Duration h: 73

ethylbenzene - CAS: 100-41-4

- a) Aquatic acute toxicity:  
Endpoint: LC50 - Species: Fish = 42.3 mg/l - Duration h: 96



## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 ml/l - Duration h: 96 - Notes: Method OECD linee guide 203

Endpoint: EC50 - Species: Daphnia > 500 mg/l - Duration h: 48 - Notes: Method Direttiva 67/548CEE allegato V,C.2

Endpoint: ErC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: Method OECD TG 209

butanone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 3220 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 520 mg/l - Duration h: 48

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 454.7 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 154 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3300 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae > 100 mg/l - Duration h: 72

sec-butyl acetate - CAS: 110-19-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 17 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 25 mg/l - Duration h: 48

Endpoint: LC50 - Species: Algae = 370 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23 mg/l - Duration h: 504

c) Bacteria toxicity:

Endpoint: EC50 - Species: Active mud = 1886 mg/l - Duration h: 6

Fatty acids, C14-18 and C16-18-unsatd., maleated - CAS: 85711-46-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 150 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: ErC50 - Species: Algae > 100 mg/l - Duration h: 72

Endpoint: EC50 - Species: Active mud > 1000 mg/l - Duration h: 3

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None known

## SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

## SECTION 14: Transport information

14.1. UN number

ADR-UN Number: 1263

IATA-Un number: 1263

IMDG-Un number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

ADR-Class: 3

ADR-Label: 3

ADR - Hazard identification number: 33





## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

|  |   |
|--|---|
| IATA-Class:  | 3   |
| IATA-Label:  | 3   |
| IMDG-Class:  | 3   |
| 14.4. Packing group  |   |
| ADR-Packing Group:   | II  |
| IATA-Packing group:  | II  |
| IMDG-Packing group:  | II  |
| 14.5. Environmental hazards  |   |
| 14.6. Special precautions for user                                       |   |
| ADR-Tunnel Restriction Code:   | 2 (D/E)   |
| IATA-Passenger Aircraft:   | 353   |
| IATA-Cargo Aircraft:   | 364   |
| IMDG-Technical name:   | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) |
| IMDG-EMS:  | F-E , <u>S-E</u>  |
| 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code | No  |

#### SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) 2015/830  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:  
None  
Where applicable, refer to the following regulatory provisions :  
Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.  
Regulation (EC) nr 648/2004 (detergents).  
Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.  
  
1999/13/EC (VOC directive)  
Directive 1999/13/CE  
  
Total Volatile Organic Compounds (typical value): 48 %  
Total Volatile Organic Carbon (typical value): 40.22 %  
Total solids content: 50.9 - 52.9 %  
  
15.2. Chemical safety assessment  
No

#### SECTION 16: Other information

Text of phrases referred to under heading 3:  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H315 Causes skin irritation.  
H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H225 Highly flammable liquid and vapour.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
H336 May cause drowsiness or dizziness.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
Paragraphs modified from the previous revision:

2. HAZARDS IDENTIFICATION  
SECTION 3: Composition/information on ingredients  
SECTION 8: Exposure controls/personal protection



## Safety Data Sheet

### ES1011 - Finitura craquelé Bianca

SECTION 11: Toxicological information  
SECTION 12: Ecological information  
SECTION 14: Transport information  
SECTION 15: Regulatory information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eighth Edition - Van Nostrand Reinold  
ACGIH - Threshold Limit Values - 2004 edition

RESTRICTED TO PROFESSIONAL USERS

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

|             |  |
|-------------|--|
| ADR:        | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| CAS:        | Chemical Abstracts Service (division of the American Chemical Society).              |
| CLP:        | Classification, Labeling, Packaging.   |
| DNEL:       | Derived No Effect Level.   |
| EINECS:     | European Inventory of Existing Commercial Chemical Substances.                       |
| GefStoffVO: | Ordinance on Hazardous Substances, Germany.  |
| GHS:        | Globally Harmonized System of Classification and Labeling of Chemicals.              |
| IATA:       | International Air Transport Association.   |
| IATA-DGR:   | Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  |
| ICAO:       | International Civil Aviation Organization.   |
| ICAO-TI:    | Technical Instructions by the "International Civil Aviation Organization" (ICAO).    |
| IMDG:       | International Maritime Code for Dangerous Goods.                                     |
| INCI:       | International Nomenclature of Cosmetic Ingredients.                                  |
| KSt:        | Explosion coefficient.   |
| LC50:       | Lethal concentration, for 50 percent of test population.                             |
| LD50:       | Lethal dose, for 50 percent of test population.                                      |
| LTE:        | Long-term exposure.  |
| PNEC:       | Predicted No Effect Concentration.   |
| RID:        | Regulation Concerning the International Transport of Dangerous Goods by Rail.        |
| STE:        | Short-term exposure.   |
| STEL:       | Short Term Exposure limit.   |
| STOT:       | Specific Target Organ Toxicity.  |
| TLV:        | Threshold Limiting Value.  |
| TWATLV:     | Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).    |
| WGK:        | German Water Hazard Class.   |
| N.A.:       | N.A.   |
| N.D.:       | N.A.   |

End of Safety Data Sheet

**Safety Data Sheet**  
**ES1011 - Finitura craquelé Bianca**

Label model

ES1011  
Finitura craquelé Bianca

**Hazard pictograms:**

Danger

**Hazard statements:**

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P370+P378 In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

**Special Provisions:**

None

**Contains**

xylene [isomer mixture]  
4-methylpentan-2-one; isobutyl methyl ketone  
Fatty acids, C14-18 and C16-18-unsatd., maleated: May produce an allergic reaction.  
Fatty acids, C18-unsatd., trimers, compds. with oleylamine: May produce an allergic reaction.



Quantity:      Company: