



Safety Data Sheet

CTE5084 - Brown walnut Stain

Safety Data Sheet dated 28/11/2018, version 40

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: Brown walnut Stain

Trade code: CTE5084

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating

1.3. Details of the supplier of the safety data sheet

Company:

Sirca S.p.A.

Address:

Viale Roma, 85

35010 S.Dono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Competent person responsible for the safety data sheet:

safety@sirca.it

1.4. Emergency telephone number

Sirca S.p.A. +39 049 9322311 (08.00 - 17.00) From Monday to Friday

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
 - ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
 - ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
 - ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards known

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Safety Data Sheet

CTE5084 - Brown walnut Stain

Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P370+P378 In case of fire: Use CO₂, Foam, Chemical powders to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

- 1-methoxy-2-propanol
- trisodium
- bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-)

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

Other Hazards:

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 75% 1-methoxy-2-propanol

REACH No.: 01-2119457435-35-xxxx, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H336

>= 7% - < 9.9% 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

REACH No.: 01-2119475108-36-xxxx, Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 3% - < 5% trisodium

bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-)

REACH No.: 01-2119969289-17-xxxx, CAS: 57693-14-8, EC: 260-906-9

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.4.2/1 Skin Sens. 1 H317

⚠ 4.1/C2 Aquatic Chronic 2 H411

Safety Data Sheet

CTE5084 - Brown walnut Stain

>= 1% - < 2% Chromate(2-),
[3-[4,5-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-3-methyl-5-oxo-1H-pyrazol-1-yl]benzenesulfonato(3-)]
[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3

CAS: 90294-40-9, EC: 290-924-2

⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.25% - < 0.5% 2-methoxypropanol

Index number: 603-106-00-0, CAS: 1589-47-5, EC: 216-455-5

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.7/1B Repr. 1B H360

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Induce vomiting only on doctor's advice

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Contact a poisons centre

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use CO₂, Foam, Chemical powders to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Combustion may liberate toxic or very toxic gases. Do not breathe fumes.

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Safety Data Sheet

CTE5084 - Brown walnut Stain

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

6.3. Methods and material for containment and cleaning up

Collect the spilled product with no-sparking tools.

Rapidly recover the product. To do so, wear a mask and protective clothing.

Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.

After the product has been recovered, rinse the area and materials involved with water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from flame and sparks. Avoid accumulating electrostatic charge.

Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Do not smoke while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety Data Sheet

CTE5084 - Brown walnut Stain

Safety electric system.

7.3. Specific end use(s)

No further recommendations. Refer to point 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-methoxy-2-propanol - CAS: 107-98-2

(OEL (IT)) - TWA: 375 mg/m³, 100 ppm - STEL: 558 mg/m³, 150 ppm - Notes: pelle

NIOSH - TWA: 360 mg/m³, 100 ppm - STEL: 540 mg/m³, 150 ppm - Notes: 15 minutes average value

EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin

ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

(OEL (IT)) - TWA(8h): 98 mg/m³, 20 ppm - STEL: 246 mg/m³, 50 ppm - Behaviour:

Binding - Notes: pelle

EU - TWA(8h): 98 mg/m³, 20 ppm - STEL: 246 mg/m³, 50 ppm - Notes: Skin

MAK - TWA: 49 mg/m³, 10 ppm

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

2-methoxypropanol - CAS: 1589-47-5

TWA (Italia) - TWA: 375 mg/m³, 100 ppm

(STEL(IE)) - TWA: 568 mg/m³, 150 ppm

DNEL Exposure Limit Values

1-methoxy-2-propanol - CAS: 107-98-2

Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 50.6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 369 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Worker Industry: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 1091 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 246 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 125 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 98 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Exposure: Human Oral - Frequency: Short Term, systemic effects

Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 426 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Safety Data Sheet

CTE5084 - Brown walnut Stain

Consumer: 147 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Consumer: 75 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 59 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 26.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
 Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 trisodium
 bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8
 Worker Industry: 24.5 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 27.78 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 14.7 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 16.7 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 8.33 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
 2-methoxypropanol - CAS: 1589-47-5
 Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 183 mg/kg - Consumer: 78 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 369 mg/m³ - Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 33 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
 PNEC Exposure Limit Values
 1-methoxy-2-propanol - CAS: 107-98-2
 Target: Fresh Water - Value: 10 mg/l
 Target: Marine water - Value: 1 mg/l
 Target: occasional emission - Value: 100 mg/l
 Target: STP - Value: 100 mg/l
 Target: Freshwater sediments - Value: 41.6 mg/kg
 Target: Marine water sediments - Value: 4.17 mg/kg
 Target: Soil (agricultural) - Value: 2.47 mg/kg
 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
 Target: Fresh Water - Value: 8.8 mg/l
 Target: Marine water - Value: 0.88 mg/l
 Target: Microorganisms in sewage treatments - Value: 463 mg/l
 Target: Freshwater sediments - Value: 34.6 mg/kg
 Target: Marine water sediments - Value: 3.46 mg/kg
 Target: Soil (agricultural) - Value: 2.33 mg/l
 Target: STP - Value: 463 mg/l
 Target: orally (secondary poisoning) - Value: 20 mg/kg
 trisodium
 bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) -

Safety Data Sheet

CTE5084 - Brown walnut Stain

CAS: 57693-14-8

Target: orally (secondary poisoning) - Value: 33.3 mg/kg

Target: Soil (agricultural) - Value: 600 mg/kg

Target: Fresh Water - Value: 3 µg/L

Target: Marine water - Value: 0.3 µg/L

Target: Freshwater sediments - Value: 3000 mg/kg

Target: Marine water sediments - Value: 300 mg/kg

Target: STP - Value: 0.781 mg/l

2-methoxypropanol - CAS: 1589-47-5

Target: Fresh Water - Value: 10 mg/l

Target: Marine water - Value: 1 mg/l

Target: occasional emission - Value: 100 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg

Target: Soil (agricultural) - Value: 2.47 mg/kg

Target: Marine water sediments - Value: 4.17 mg/kg

8.2. Exposure controls

Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Because of the synergetic effect of the substances contained in the formulation it is not possible to identify a unique material that can resist to their fusion. Multi - layer protective gloves can be suitable for mixes of substances. Pay attention to the data about grade of protection and of permeation rate furnished by the producer of the gloves about the substances listed on point 3 of this sheet.

Respiratory protection:

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

Thermal Hazards:

None known

Environmental exposure controls:

None known

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1°C
Initial boiling point and boiling range:	> 55°C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	23°C ≤ fp ≤ 60°C
Evaporation rate:	N.A.

Safety Data Sheet

CTE5084 - Brown walnut Stain

Vapour pressure: N.A.
 Relative density: 0.9400 Kg/l a 20°C
 Solubility in water: N.A.
 Solubility in oil: N.A.
 Partition coefficient (n-octanol/water): N.A.
 Auto-ignition temperature: > 250°C
 Decomposition temperature: N.A.

Explosive properties: N.A.
 Oxidizing properties: N.A.

9.2. Other information

Miscibility: N.A.
 Fat Solubility: N.A.
 Conductivity: N.A.
 Substance Groups relevant properties N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
 - No dangerous reaction is stored and used appropriately.
- 10.4. Conditions to avoid
 - Avoid accumulating electrostatic charge.
 - Vapours can form explosive mixtures with air.
- 10.5. Incompatible materials
 - Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products
 - vapours potentially dangerous to health may be released.

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects
 - Toxicological information of the product:
 - N.A.
 - Toxicological information of the main substances found in the product:
 - 1-methoxy-2-propanol - CAS: 107-98-2
 - a) acute toxicity:
 - Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg
 - Test: LC0 - Route: Inhalation Vapour - Species: Rat > 7000 Ppm - Duration: 6h
 - Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
 - b) skin corrosion/irritation:
 - Test: Skin Irritant Negative
 - c) serious eye damage/irritation:
 - Test: Eye Irritant Negative
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
 - a) acute toxicity:
 - Test: LD50 - Route: Oral - Species: Cavia porcellus 1300 mg/kg
 - Test: LD50 - Route: Skin - Species: Cavia porcellus > 2000 mg/kg

Safety Data Sheet

CTE5084 - Brown walnut Stain

Test: LC50 - Route: Inhalation Vapour - Species: Cavia porcellus > 400 Ppm - Duration: 7h

Test: LD50 - Route: Skin - Species: Rat 220 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Species: Rabbit Yes - Notes: Provoca irritazione cutanea

Test: Eye Irritant - Species: Rabbit Yes - Notes: provoca grave irritazione oculare

trisodium

bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg body weight - Source: OECD402

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

1-methoxy-2-propanol - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 6800 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia > 23300 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 168 - Notes: - (7d)

f) Effects in sewage plants:

Endpoint: EC50 - Species: Active mud > 1000 mg/l - Duration h: 3

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1490 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 24

c) Bacteria toxicity:

Endpoint: EC50 - Species: Active mud > 700 mg/l - Duration h: 16

trisodium

bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 30.2 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 3 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae 73.8 mg/l - Duration h: 72

Chromate(2-),

[3-[4,5-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-3-methyl-5-oxo-1H-pyrazol-1-yl]

Safety Data Sheet

CTE5084 - Brown walnut Stain

benzenesulfonato(3-)[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3 - CAS: 90294-40-9

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1 mg/l - Duration h: 96

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

SECTION 14: Transport information

14.1. UN number

ADR-UN Number: 1263

IATA-Un number: 1263

IMDG-Un number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

ADR-Class: 3

ADR-Label: 3

ADR - Hazard identification number: 33

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Safety Data Sheet

CTE5084 - Brown walnut Stain

14.6. Special precautions for user

ADR-Tunnel Restriction Code: 2 (D/E)

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IMDG-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-EMS: F-E , S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.

1999/13/EC (VOC directive)

Directive 1999/13/CE

Total Volatile Organic Compounds (typical value): 93 %

Total Volatile Organic Carbon (typical value): 49.73 %

Total solids content: 6.9 - 7.1 %

Total Volatile Organic Compounds (typical value): 874.2 gr/l

15.2. Chemical safety assessment

No

Safety Data Sheet

CTE5084 - Brown walnut Stain

SECTION 16: Other information

Text of phrases referred to under heading 3:

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H319 Causes serious eye irritation.
- H315 Causes skin irritation.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H332 Harmful if inhaled.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.
- H360 May damage fertility or the unborn child.
- H335 May cause respiratory irritation.
- H318 Causes serious eye damage.

Paragraphs modified from the previous revision:

SECTION 9: Physical and chemical properties

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eighth Edition - Van Nostrand Reinold
- ACGIH - Threshold Limit Values - 2004 edition

RESTRICTED TO PROFESSIONAL USERS

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.



Safety Data Sheet

CTE5084 - Brown walnut Stain

LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	

End of Safety Data Sheet

Safety Data Sheet

CTE5084 - Brown walnut Stain

Label model

CTE5084

Brown walnut Stain



Hazard pictograms:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378 In case of fire: Use CO₂, Foam, Chemical powders to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

1-methoxy-2-propanol
trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-)

Quantity:	Company:
------------------	-----------------
