



Safety Data Sheet

FWE600 - Fondo trasparente per esterni all'acqua

Safety Data Sheet dated 19/6/2017, version 31

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: Fondo trasparente per esterni all'acqua

Trade code: FWE600

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating

1.3. Details of the supplier of the safety data sheet

Company:

Sirca S.p.A.

Address:

Viale Roma, 85

35010 S. Dono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Competent person responsible for the safety data sheet:

safety@sirca.it

1.4. Emergency telephone number

Sirca S.p.A. +39 049 9322311 (08.00 - 17.00) From Monday to Friday

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards known

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

EUH210 Safety data sheet available on request.

Contains

1,2-benzisothiazol-3(2H)-one: May produce an allergic reaction.

5-chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

Safety Data Sheet

FWE600 - Fondo trasparente per esterni all'acqua

None
2.3. Other hazards

Other Hazards:
No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances
N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:
≥ 3% - < 5% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether
REACH No.: 01-2119475104-44-xxxx, Index number: 603-096-00-8, CAS: 112-34-5, EC:
203-961-6
⚠ 3.3/2 Eye Irrit. 2 H319

≥ 0.0015% - < 0.05% 1,2-benzisothiazol-3(2H)-one
Index number: 613-088-00-6, CAS: 2634-33-5, EC: 220-120-9
⚠ 3.2/2 Skin Irrit. 2 H315
⚠ 3.3/1 Eye Dam. 1 H318
⚠ 3.4.2/1 Skin Sens. 1 H317
⚠ 4.1/A1 Aquatic Acute 1 H400
⚠ 3.1/4/Oral Acute Tox. 4 H302

< 0.0015% 5-chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone
Index number: 613-167-00-5, CAS: 55965-84-9
⚠ 3.1/3/Oral Acute Tox. 3 H301
⚠ 3.1/3/Dermal Acute Tox. 3 H311
⚠ 3.1/3/Inhal Acute Tox. 3 H331
⚠ 3.2/1B Skin Corr. 1B H314
⚠ 3.4.2/1 Skin Sens. 1 H317
⚠ 4.1/A1 Aquatic Acute 1 H400 M=10.
⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Induce vomiting only on doctor's advice

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Safety Data Sheet

FWE600 - Fondo trasparente per esternali'acqua

- 4.2. Most important symptoms and effects, both acute and delayed
Contact a poisons centre
- 4.3. Indication of any immediate medical attention and special treatment needed
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
Suitable extinguishing media:
Water.
Carbon dioxide (CO₂).
Extinguishing media which must not be used for safety reasons:
None in particular.
- 5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.
After the product has been recovered, rinse the area and materials involved with water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not eat or drink while working.
Do not smoke while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:

Safety Data Sheet

FWE600 - Fondo trasparente per esternali'acqua

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Keep from freezing

7.3. Specific end use(s)

No further recommendations. Refer to point 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

(OEL (IT)) - TWA(8h): 67.5 mg/m³, 10 ppm - STEL: 101.2 mg/m³, 15 ppm - Behaviour: Binding

EU - TWA(8h): 67.5 mg/m³, 10 ppm - STEL: 101.2 mg/m³, 15 ppm

ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff

DNEL Exposure Limit Values

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Worker Industry: 67.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 67.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 20 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 101.2 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 34 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 50.6 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 10 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.25 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Target: Fresh Water - Value: 1 mg/l

Target: Marine water - Value: 0.1 mg/l

Target: occasional emission - Value: 3.9 mg/l

Target: STP - Value: 200 mg/l

Target: Freshwater sediments - Value: 4 mg/kg dwt

Target: Marine water sediments - Value: 0.4 mg/kg dwt

Target: Soil (agricultural) - Value: 0.4 mg/kg dwt

Target: orally (secondary poisoning) - Value: 56 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

Not needed for normal use. Work, in any case, in accordance with good practices of industrial hygiene.

Protection for hands:

Not needed for normal use. Work, in any case, in accordance with good practices of industrial

Safety Data Sheet

FWE600 - Fondo trasparente per esterni all'acqua

hygiene.

Respiratory protection:

Not needed for normal use. Work, in any case, in accordance with good practices of industrial hygiene.

Thermal Hazards:

None known

Environmental exposure controls:

None known

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1°C
Initial boiling point and boiling range:	> 55°C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	other (≥ 60°C ; > 140°F)
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.0300 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250°C
Decomposition temperature:	N.A.
Viscosity (typical value):	15000.00 cPs Brookfield
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Safety Data Sheet

FWE600 - Fondo trasparente per esterni all'acqua

None in particular.

- 10.6. Hazardous decomposition products
vapours potentially dangerous to health may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rabbit = 3 mg/l - Duration: 2h

Test: LD50 - Route: Oral - Species: Rat = 5660 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 2700 mg/kg

Test: LD50 - Route: Oral - Species: Mouse = 2400 mg/kg

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1193 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg

5-chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone - CAS: 55965-84-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h - Notes: aerosol

Test: LD50 - Route: Skin - Species: Rabbit = 660 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 457 mg/kg

b) skin corrosion/irritation:

Test: Skin Corrosive - Species: Rabbit Yes

c) serious eye damage/irritation:

Test: Eye Corrosive - Species: Rabbit Yes

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Yes

Test: Inhalation Sensitization - Route: Inhalation - Species: Cavia porcellus Yes

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Safety Data Sheet

FWE600 - Fondo trasparente per esternali'acqua

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1300 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 100 mg/l - Duration h: 48

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48

Endpoint: ErC50 - Species: Algae = 0.11 mg/l - Duration h: 72

5-chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 0.19 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 0.16 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.027 mg/l - Duration h: 72

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)

Safety Data Sheet

FWE600 - Fondo trasparente per esternali'acqua

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.

1999/13/EC (VOC directive)

Directive 1999/13/CE

Total Volatile Organic Compounds (typical value): 4 %

Total Volatile Organic Carbon (typical value):

1.87 %

Total amount of water 58.6 - 60.8 %

Total solids content: 35.7 - 37.1 %

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H302 Harmful if swallowed.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H410 Very toxic to aquatic life with long lasting effects.

Paragraphs modified from the previous revision:

SECTION 3: Composition/information on ingredients

This document was prepared by a competent person who has received appropriate training.

Safety Data Sheet

FWE600 - Fondo trasparente per esternalità acqua

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eighth Edition - Van
Nostrand Reinhold

ACGIH - Threshold Limit Values - 2004 edition

RESTRICTED TO PROFESSIONAL USERS

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	

End of Safety Data Sheet



Safety Data Sheet

FWE600 - Fondo trasparente per esterni all'acqua

Label model

FWE600

Fondo trasparente per esterni all'acqua

Hazard pictograms:

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

EUH210 Safety data sheet available on request.

Contains

1,2-benzisothiazol-3(2H)-one: May produce an allergic reaction.

5-chloro-2-methyl-3(2H)-isothiazolone with 2-methyl-3(2H)-isothiazolone: May produce an allergic reaction.

Quantity:

Company:
